

# TC52 and TC57 Series Touch Computer

# The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



# The ultimate user experience

# Android for instant familiarity

Your workers already know how to use an Android device, virtually eliminating training time and adoption curves. And you can deliver the highly-graphic interactive apps today's workers expect.

# Advanced touchscreen technology

Give your workers touchscreen simplicity. The 5 in. display offers plenty of real estate for graphics-intensive intuitive applications. The easy, familiar and flexible multi-touch operation works even when wet, with a gloved finger or a stylus. And with best-in-class outdoor readability, the screen is easy to read, even in bright sunlight.

# Easily capture it all — barcodes, labels and documents

Advanced scanning technology and PRZM Intelligent Imaging deliver lightning fast capture of printed and electronic 1D and 2D barcodes, including Digimarc — regardless of condition. The expanded working range and wide field of view allow workers to scan barcodes nearer and farther away, while omnidirectional scanning delivers true point and shoot performance — no need to ever align the device with the barcode. Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

# Full shift power your workers can count on

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>2</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

# Active Edge<sup>™</sup> Touch Zone for One-touch Feature Access

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

# All the latest technology advancements

# Rugged and ready for the toughest business day

While these touch computers look like smartphones, the similarities stop there — they are engineered for the enterprise, inside and out. You can drop it in water or on concrete and use it in dusty areas, out in the rain or snow — and still expect reliable operation. The unibody design provides extra impact protection for the sensitive electronics. And the Corning Gorilla Glass touch panel and imager window bring maximum scratch-resistance and shatter-proofing to two of the most vulnerable device features.



# The TC52/TC57 — The ultimate enterprise touch computer.

# greenŖ-id

www.greenrx-id.com info@greenrx-id.com

## A platform to handle all your apps — today and tomorrow

The ultra-powerful processor provides superior performance on all voice and data apps. You also get built-in support for the next two versions of Android (P and Q)<sup>1</sup> and future apps, such as artificial intelligence.

## **Rich locationing support**

Easily implement locationing with support for many technologies, including Visible Light Communication (VLC), Bluetooth 5.0 BLE and WiFi, plus Zebra's SmartLens<sup>3</sup> and MotionWorks solutions.

# Support for the latest WiFi enhancement

improves WiFi range and speed — with less power

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

# The highest quality voice in its class

Three microphones, high-volume speakers and noise-cancellation technology work together to ensure that callers on both ends of every call can hear every word — even in the noisiest areas.

# New 5 MP front-facing camera supports more advanced apps With

the new front-facing camera, you get built-in support for the latest positioning technology, Visible Light Communication (VLC) which allows you to track the location of shoppers and workers with compatible overhead LED lighting. Video calling improves service and productivity. Customers enjoy a more personal touch — and remote experts can see a repair in process to help onsite technicians resolve issues faster and increase first-time-fix rates.

### Complete cellular network flexibility with single device simplicity

The TC57 provides all workers anywhere in the world with dependable cellular service. Support for carrier aggregation substantially improves application performance by increasing data capacity and speeds. And support for the powerful Public Safety LTE network provides the reliable communications first responders need, eliminating network congestion concerns and providing the interagency operation required for improved situational awareness.

# Ultra high-resolution photos and videos

The 13 MP color rear camera captures highly detailed photos and videos — ideal for proof-of-condition/delivery/service, onsite technical support and more.

# Bluetooth 5.0 for twice the speed and four times the range — with less power

Improved data speeds up to 2 Mbps increases application flexibility and performance for Bluetooth peripherals, such as printers and headsets, while Bluetooth Low Energy reduces power requirements to extend battery cycle times.

### Maximize productivity with enterprise accessories

Unlike consumer smartphones, you get a full suite of backward compatible business-class accessories that make the TC52/TC57 easier to use and manage, from a snap-on trigger handle for easier scanning to unique ShareCradles that charge it all — devices and batteries.

# Drive workforce productivity, efficiency and device value to a new level with powerful new Mobility DNA apps

## WorryFree WiFi - dependably superior WiFi, delivered

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

# PowerPrecision Console — prevent aging batteries from reducing workforce productivity

This free PC-based solution provides an easy-to-read dashboard that allows you to quickly identify and remove aging batteries from your battery pool — before they impact workforce productivity and mobile device uptime.

# End-to-end revolutionary control of the update process with LifeGuard

Updating your enterprise-class Android mobile devices is often time-consuming, costly, complex and difficult to track. Now you can do it all with LifeGuard Analytics — free with your Zebra OneCare Support contract. View available updates along with priority and which devices are eligible for the update. Automatically update your devices over the air with the press of a button. And easily monitor and manage the status of updates in real time.

# Easily manage access to Google Mobile Services (GMS) with Restricted Mode

StageNow's new Restricted Mode delivers an industry first — an easy way to simply click to deactivate Google Mobile Services (GMS) that come standard with the operating system — and reactivate should you need them down the road. StageNow is free and pre-loaded on every TC52/TC57.

# The ultimate in device management options

## Improve device value with Zebra's optional Visibility Services

Get the device management data you need to take device uptime, operational efficiency and the return on investment to the next level. Asset Visibility Service (AVS) is an easy to use and deploy solution that doesn't require an Enterprise Mobility Management (EMM) system. Operational Visibility Services (OVS) is a comprehensive device management solution that leverages your EMM information to help get more value out of your Zebra mobile devices. These optional services can be added to your optional Zebra OneCare support contract.<sup>3</sup>



# TC52/TC57 Series Specifications

Dimensions6.1 in. L x 2.9 in. W x 0.73 in. H 155 mm U x 75.5 mm W x 18.6 mm HWeight8.8 oz./249 g with batteryDisplay5.0 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panelImager WindowCorning Gorilla GlassTouchpanelDual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus soid separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti- smudge coatingBacklightLED backlightPowerRechargeable Li-Ion, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)Expansion SlotUser accessible MicroSD up to 32GB SDHC and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetworkTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless heads support; cellular circuit switch voice; HD Voice; and SW8 & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, duid dedicated sca buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUOperating Temp4*F to 122*F/-20*C to 50*CStorage Temp40*F to 158*F/-40*C to 70*CHumidity5% to 95% non-condensing<	PHYSICAL CHARACTERISTICS		
Display     5.0 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel       Imager Window     Corning Gorilla Glass       Touchpanel     Dual mode capacitive touch with stylus or bare or gloved fingerip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant antismudge coating       Backlight     LED backlight       Power     Rechargeable Li-lon, PowerPrecision + 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V; management; fast USB charging (500 mA)       Expansion Slot     User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC       SIM Slots     TC57 only: 1 nano SIM       Network     TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, Connections       High Speed (Host and Client)     TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, Connections       High Speed (Host and Client)     TC57 Only: WWAN       Notification     Audible tone; multi-color LEDs; vibration       Keypad     On-screen keypad and enterprise keyboard       Voice and Audio     Three microphones with noise cancellation; vibrate altert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio       Buttons     Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons <th>Dimensions</th> <th></th>	Dimensions		
bright, outdoor viewable; optically bonded to touch panelImager WindowCorning Gorilla GlassTouchpanelDual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti- smudge coatingBacklightLED backlightPowerRechargeable Li-lon, PowerPrecision +, 4300mAh/5.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)Expansion SlotUser accessible MicroSD up to 32GB SDHC and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetworkTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker, Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPU Qualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating Temp4°F to 158°F/-40°C to 50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsSout 12°F/-20°C to 50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidity5% to 95% non-con	Weight	8.8 oz./249 g with battery	
TouchpanelDual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti- smudge coatingBacklightLED backlightPowerRechargeable LI-Ion, PowerPrecision +, 4300mAh/15,48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)Expansion SlotUser accessible MicroSD up to 32GB SDHC and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetworkTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated cac no tutons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUOperating Temp4°F to 152°F/-20°C to 50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 41/1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft, drops to concrete with the rugged boot accessory per MIL STD 810 GTumble SpecificationsSultiples, perticationSealingIP67 and IP65 per applicable IEC sealing specifications	Display	bright, outdoor viewable; optically bonded to	
or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti- smudge coatingBacklightLED backlightPowerRechargeable Li-Ion, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)Expansion SlotUser accessible MicroSD up to 32GB SDHC and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetworkTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SW& & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated can buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUOperating Temp4°F to 152°F/-20°C to 50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 411.12 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 61. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble SpecificationsMultiple 41.02 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 61. drops to concrete with the rugged boot accessory per MIL STD 810 GStora	Imager Window	Corning Gorilla Glass	
Power   Rechargeable Li-lon, PowerPrecision +, 4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)     Expansion Slot   User accessible MicroSD up to 32GB SDHC and up to 256 GB SDXC     SIM Slots   TC57 only: 1 nano SIM     Network   TC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWAN     Notification   Audible tone; multi-color LEDs; vibration     Keypad   On-screen keypad and enterprise keyboard     Voice and Audio   Three microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audio     Buttons   Six programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttons     PERFORMANCE CHARACTERISTICS   CPU     CPU   Qualcomm Snapdragon <sup>min</sup> 660 octa-core, 2.2 GHz     Operating System   Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services     Memory   4GB RAM/32GB Flash     USER ENVIRONMENT   Operating Temp.     Operating Temp.   -4°F to 122°F/-20°C to 50°C     Storage Temp.   -40°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing	Touchpanel	or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti-	
4300mÅh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery management; fast USB charging (500 mA)Expansion SlotUser accessible MicroSD up to 32GB SDHC and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetwork ConnectionsTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Ohly: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon " 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENTOperating Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble SpecificationS001.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationSealingIP67 and IP65 per applicable IEC sealing specifications	Backlight	LED backlight	
and up to 256 GB SDXCSIM SlotsTC57 only: 1 nano SIMNetwork ConnectionsTC57 Only: UAAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon <sup>™</sup> 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENT-4°F to 122°F/-20°C to 50°CStorage Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specification500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Power	4300mAh/15.48Wh typical, 4.2V Cell Charge voltage, Cell nominal voltage 3.6V, Improved battery metrics for better battery	
Network ConnectionsTC52/TC57: WLAN, WPAN (Bluetooth), USB 2.0, High Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; wibrate alert; Front facing speaker, Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: 	Expansion Slot		
ConnectionsHigh Speed (Host and Client) TC57 Only: WWANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker, Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB &FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENTOperating Temp4°F to 122°F/-20°C to 50°CStorage Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specification500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationSealingIP67 and IP65 per applicable IEC sealing specificationsVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	SIM Slots	TC57 only: 1 nano SIM	
KeypadOn-screen keypad and enterprise keyboardVoice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENT-4°F to 122°F/-20°C to 50°CStorage Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specification500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random		High Speed (Host and Client)	
Voice and AudioThree microphones with noise cancellation; vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon" 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENTOperating Temp4°F to 152°F/-20°C to 50°CStorage Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specification500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationSealingIP67 and IP65 per applicable IEC sealing specificationsVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Notification	Audible tone; multi-color LEDs; vibration	
vibrate alert; Front facing speaker; Bluetooth wireless headset support; cellular circuit switch voice; HD Voice; and SWB & FB audioButtonsSix programmable buttons for maximum flexibility: Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENTOperating Temp4°F to 122°F/-20°C to 50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble SpecificationsS00 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationSealingIP67 and IP65 per applicable IEC sealing specificationsVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Keypad	On-screen keypad and enterprise keyboard	
Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume up/down buttonsPERFORMANCE CHARACTERISTICSCPUQualcomm Snapdragon™ 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENT-4°F to 122°F/-20°C to 50°COperating Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specifications500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Voice and Audio	vibrate alert; Front facing speaker; Bluetooth wireless headset support; High quality speaker phone; PTT headset support; cellular circuit switch	
CPUQualcomm Snapdragon" 660 octa-core, 2.2 GHzOperating SystemAndroid 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other servicesMemory4GB RAM/32GB FlashUSER ENVIRONMENT-4°F to 122°F/-20°C to 50°COperating Temp4°F to 158°F/-40°C to 70°CHumidity5% to 95% non-condensingDrop SpecificationsMultiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 GTumble Specification500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specificationSealingIP67 and IP65 per applicable IEC sealing specificationsVibration4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Buttons	Back button, dual dedicated scan buttons, dedicated push-to-talk button and volume	
Operating System   Android 8.1 Oreo with Zebra's Restricted Mode for control over GMS and other services     Memory   4GB RAM/32GB Flash     USER ENVIRONMENT   -4°F to 122°F/-20°C to 50°C     Storage Temp.   -4°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	PERFORMANCE CHARA	CTERISTICS	
control over GMS and other services     Memory   4GB RAM/32GB Flash     USER ENVIRONMENT   -4°F to 122°F/-20°C to 50°C     Storage Temp.   -4°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz	
USER ENVIRONMENT     Operating Temp.   -4°F to 122°F/-20°C to 50°C     Storage Temp.   -40°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Operating System		
Operating Temp.   -4°F to 122°F/-20°C to 50°C     Storage Temp.   -40°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Memory	4GB RAM/32GB Flash	
Storage Temp.   -40°F to 158°F/-40°C to 70°C     Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	USER ENVIRONMENT		
Humidity   5% to 95% non-condensing     Drop Specifications   Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G     Tumble Specification   500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification     Sealing   IP67 and IP65 per applicable IEC sealing specifications     Vibration   4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Operating Temp.	-4°F to 122°F/-20°C to 50°C	
Drop Specifications     Multiple 4 ft./1.2 m to tile over concrete over -10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the rugged boot accessory per MIL STD 810 G       Tumble Specification     500 1.6 ft./0.5 m tumbles, meets or exceeds IEC tumble specification       Sealing     IP67 and IP65 per applicable IEC sealing specifications       Vibration     4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Storage Temp.	-40°F to 158°F/-40°C to 70°C	
-10°C to 50°C (14°F to 122°F)     Multiple 6ft. drops to concrete with the     rugged boot accessory per MIL STD 810 G     Tumble Specification     500 1.6 ft./0.5 m tumbles, meets or exceeds IEC     tumble specification     Sealing     Vibration     4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Humidity	5% to 95% non-condensing	
tumble specification   Sealing IP67 and IP65 per applicable IEC sealing specifications   Vibration 4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Drop Specifications	-10°C to 50°C (14°F to 122°F) Multiple 6ft. drops to concrete with the	
specifications       Vibration     4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random	Tumble Specification		
	Sealing		

USER ENVIRONMENT (C	CONTINUED)	
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition	
Electrostatic Discharge (ESD)	+/- 15kv air discharge; +/- 8kv direct discharge; +/- 8kv indirect discharge	
INTERACTIVE SENSOR 1	ECHNOLOGY (IST)	
Light Sensor	Automatically adjusts display backlight brightness	
Magnetometer	eCompass automatically detects direction and orientation	
Motion Sensor	3-axis Accelerometer with MEMS Gyro	
Pressure Sensor	Automatically detects altitude information for locating (TC57 only)	
Proximity Sensor	Automatically detects when the user places the handset against head during a phone call to disable display output and touch input	
DATA CAPTURE		
Scanning	SE4710 imager (1D and 2D) with extraordinary range: Scan range – Code 39 barcode: 20 Mil: 1.8 in. to 32.0 in./4.5 cm to 81.3 cm 3 Mil: 3.1 in. to 5.6 in./7.9 cm to 14.2 cm Digimarc support	
Camera	Front — 5 MP; f/2.0 aperture Rear — 13 MP autofocus; f/2.2 aperture; flash LED generates balanced white light; supports Torch mode	
NFC	ISO 14443 Type A and B; FeliCa and ISO 15693 cards; P2P mode and Card Emulation via Host. TC57 Only: Card Emulation via Host and UICC	
WIRELESS WAN DATA AND VOICE COMMUNICATIONS (TC57 ONLY)		
Radio Frequency Band	Supports VoLTE , Carrier Aggregation up to 3DL CA LTE FDD: 700/800/850/900/1800/1900/ AWS/2100/2600 (28,13,14,12,17/19,20/5,26/8/3/2, 25/4,66/1/7); LTE TDD: 1900/2300/2500 (39/40/41,38); UMTS/HSPA/HSPA+: 850/900/AWS/1900/2100 (5/8/4/2/1); GSM/GPRS/EDGE: 850/900/1800/1900	
GPS	TC57 only: Autonomous, Concurrent GPS; GLONASS; Gallileo; BeiDou, and A-GPS. Supports IZAT <sup>™</sup> XTRA	
Multimedia	Wi-Fi Multimedia <sup>™</sup> (WMM) and WMM-PS; Including TSPEC	
WIRELESS LAN		
Radio	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v <sup>3</sup> /w; Wi-Fi <sup>™</sup> certified; IPv4, IPv6, 2x2 MU-MIMO TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v <sup>3</sup> /w; Wi-Fi <sup>™</sup> certified; IPv4, IPv6, 5GHz 2x2 MU-MIMO	
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps	
Operating Channels	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11,12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52 56,60,64,100,104,108,112,116,120,124,128,132,136,14 0,144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency.	
	Continued on page	

# TC52/TC57 Series vertical markets and applications:

# RETAIL ASSOCIATES

- Price/inventory Checks
- Loyalty apps
- Item locator
- Price management
- Line busting/POS
- Assisted selling
- Electronic coupons
- Store transfers
- Gift registry lookup

# RETAIL MANAGERS

- Workforce management
- Planogram management
- Promotion compliance
- Merchandising

## DIRECT STORE DELIVERY DRIVERS

- Order automatiion
- Delivery tracking
- Inventory management
- Customer support

### FIELD SERVICE TECHNICIANS

- Asset management
- Parts inventory
- Invoicing
- Scheduling and location-based services

### LIGHT COURIER DRIVERS

- Proof of delivery
- Asset management
- Location services
- Invoicing

green**R-Id** 

\_

\_

# TC52/TC57 Specifications (continued)

WIRELESS LAN (CONTINUED)	
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP.EAP-PWD
Certifications	WFA (802.11n, WMM-PS, 801.11ac, PMF)
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC
WIRELESS PAN	
Bluetooth	Class 2, Bluetooth v5.0, Bluetooth Low Energy (BLE)

# WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the TC52/57 Series is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: www.zebra.com/warranty

### **RECOMMENDED SERVICES**

Zebra OneCare Essential and Select support services Zebra Visibility Services — Asset Visibility Service (AVS) and Operational Visibility Service (OVS) $^3$ 

1. Upgrading to new supported versions of Android requires the purchase of  $% \mathcal{A}(\mathcal{A})$ 

a Zebra OneCare Service contract 2. Based on typical user profiles

3. Available Q1 2019

Specifications subject to change without notice.



# MOBILITY DNA SOFTWARE

Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna



Mobility DNA is available on Android only. Features may vary by model and a Support Contract may be required. To learn what solutions are supported, please visit: https://developer.zebra.com/mobilitydna

